



EUROCEL 201 TPL

Short description:

Single sided general purpose tape

Product Data

Backing:	LDPE film laminated with cloth, available in several colours
Adhesive:	synthetic rubber
Total thickness	0.185 mm
Adhesion to steel	16 N/25mm
Tensile strength MD	100 N/25mm
Elongation at break	15 %
Temp. Resistance	60 °C

Application

General purpose single sided tape, suitable for binding of insulation covers such as pipes and panels, also fit for general packaging and “emergency” mending of sunshades, etc.

Features	Benefits
Synthetic rubber adhesive	<ul style="list-style-type: none"> ➤ Good adhesion on irregular surfaces ➤ High performance on several materials
Laminated cloth LDPE backing	<ul style="list-style-type: none"> ➤ Highly conformable ➤ Suitable for several kinds of applications ➤ Available in a wide range of colour ➤ Hand tearable

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use.

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
 Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;
 E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss